



## DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No. 305/2011

Name of the product

**VANDEX REFURBISHMENT PLASTER white**

No. 077

1. Unique identification code of the product-type:  
**EN 998-1:ZA.1**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):  
batch number: see packaging of the product
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**Renovation mortar for rendering/plastering of humid and/or salt containing internal and external walls, ceilings, columns and partitions**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  
**Vandex Isoliermittel-Gesellschaft m.b.H.  
Industriestraße 19-23  
DE-21493 Schwarzenbek**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 4**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**EN 998-1:2010, System 4:**  
not relevant
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
not relevant

9. Declared performance

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonised Technical specification</i>
Reaction to fire	class A1	EN 998-1:2010
Water absorption	$\geq 0.3 \text{ kg/m}^2$ after 24 h	
Water vapour permeability	$\mu \leq 15$	
Adhesion	0.25 N/mm <sup>2</sup> fracture pattern B	
Thermal conductivity	$\lambda_{10,\text{dry,mat}} \leq 0.45 \text{ W/(m} \cdot \text{K)}$ (tab. mean value; P = 50%)	
Durability (against freeze/thaw)	evaluation based on provisions valid in the intended place of use of the mortar	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Schwarzenbek, 01.07.2013

Christian Biner, Managing Director

Edition: July 2013

Annex: Certificate of conformity of the factory production control